

# ZHEJIANG DEJIA NEW MATERIAL CO.,LTD



## TECHNICAL DATA SHEET

**Product:** -PVC plain weave double side coated Fabric (9992)

**Application:**

Membrane structure

|                                    |                             |
|------------------------------------|-----------------------------|
| Support Cloth ( DIN 6000 )         | Polyester                   |
| Specification ( DIN EN 1049-2 )    | 15*16 per inch(plain weave) |
| Yarn (dtex) ( DIN EN ISO 2060 )    | 1000*1000 D                 |
| Type of Coating                    | pvc coated on both sides    |
| Total Weight ( DIN EN ISO 2286-2 ) | 1050g/m <sup>2</sup>        |
| Width ( DIN EN ISO 2286-1)         | UP TO 3.2M                  |
| Tensile strength ( DIN 53354 )     | 4500/4200 N/5CM             |
| Tear strength ( DIN 53356 )        | 600/500N/5CM                |
| Adhesion Strength                  | 120N/5CM                    |
| Low Temperature-No Crack At        | -30°C to +70°C              |
| Flame Retardant                    | NFPA701,M2,B1               |

**Packing:** craft paper or PE foam

**Features:**

- A: UV resistant , FR (NFPA701,B1,M2
- B: Cold resistant, Anti-Mildow
- C: Glossy and Matt surface
- D: Lacquered are available as requests
- E: Color, weight can be customized