®ZHEJIANG DEJIA NEW MATERIAL CO.,LTD
No.1 Luhong Road, Dingqiao, Haining, Zhejiang, China. 314413
www.dejiafabric.com

TECHNICAL DATA SHEET

Product: -TPU plain weave double side coated Fabric (9207 1100gr/m2)

Air tight, high performance

Application:

Water Tank, air tight products

Support Cloth (DIN 6000)	Polyester
Specification (DIN EN 1049-2)	36*36 per inch/14.4*14.4/CM (panama weave)
Yarn (Daniel) (DIN EN ISO 2060)	1000*1000 D
Type of Coating	TPU coated on both sides
Total Weight (DIN EN ISO 2286-2)	1100g/m2 32oz
Width (DIN EN ISO 2286-1)	1 to3.5m /39-137inch
Tensile strength (DIN 53354)	6200/6000 N/5CM
Tear strength (DIN 53356)	500/450 N/5CM
Adhesion Strength	280N/5CM
Low Temperature-No Crack At	-50℃ to +80℃
Lacquer	NA
Flame Retardant	General
UV (QUV)	1500Hours
Environmental protective	Drinkable/Direct contact food

Packing: craft paper or PE foam, Jumbo rolls 200m, 300m available

Features:

A: UV resistant

B: Cold resistant, Anti-Mildew and bacterial

C: Glossy, semi glossy and Matt surface

D: Low leak

E: Color, weight can be customized