



ZHEJIANG DEJIA NEW MATERIAL CO.,LTD

No.1 Luhong Road, Dingqiao, Haining, Zhejiang, China. 314413

www.dejiafabric.com

TECHNICAL DATA SHEET

Product: -PVC plain weave double side coated Fabric (6102 450gr/m2)

Application:

Tarpaulin/ General Cover

Support Cloth (DIN 6000)	Polyester
Specification (DIN EN 1049-2)	20*20 per inch(plain weave)
Yarn (d) (DIN EN ISO 2060)	1000*1000 D
Type of Coating	PVC coated on both sides
Total Weight (DIN EN ISO 2286-2)	450g/m2
Width (DIN EN ISO 2286-1)	UP TO 3.2M (Common Width 1.55, 2.05, 2.5, 3m)
Tensile strength (DIN 53354)	2300/2200 N/5CM
Tear strength (DIN 53356)	260/250N/5CM
Adhesion Strength	100/5cm
Low Temperature-No Crack At	-30°C to +70°C
Flame Retardant	NFPA701, M2, B1 as request

Packing: craft paper or PE foam, available with Hard Tube protection packing.

Features:

A: UV resistant, FR (NFPA701, B1, M2)

B: Cold resistant, Anti-Mildew

C: Glossy and Matt surface

D: Lacquered are available as requests

E: Color, weight can be customized