®ZHEJIANG DEJIA NEW MATERIAL CO.,LTD
No.1 Luhong Road, Dingqiao, Haining, Zhejiang, China. 314413
www.dejiafabric.com

TECHNICAL DATA SHEET

Product: -PVC Coated Tent Fabric (7703 650gr/m2) Translucent

Application:

Tents, Roof

Support Cloth (DIN 6000)	Polyester
Specification (DIN EN 1049-2)	20*20 per inch(plain weave)
Yarn (d) (DIN EN ISO 2060)	1000*1000 D
Type of Coating	PVC coated on both sides
Total Weight (DIN EN ISO 2286-2)	650g/m2
Width (DIN EN ISO 2286-1)	UP TO 3.2M (Common Wdith2.5, 3m)
Tensile strength (DIN 53354)	2700/2600 N/5CM
Tear strength (DIN 53356)	280/270N/5CM
Adhesion Strength	100/5cm
Lacquer	Acrylic or PVDF
UV(QUV)	1500hours
Anti-mildew	Grade 0
Low Temperature-No Crack At	-30℃ to +70℃
Flame Retardant	NFPA701,M2,B1 as request

Packing: craft paper or PE foam, available with Hard Tube protection packing.

Features:
A: UV resistant, FR (NFPA701, B1, M2)
B: Cold resistant, Anti-Mildew
C: Glossy and Matt surface
D: Lacquered are available as requests
E: Color, weight can be customized