®ZHEJIANG DEJIA NEW MATERIAL CO.,LTD
No.1 Luhong Road, Dingqiao, Haining, Zhejiang, China. 314413
www.dejiafabric.com

TECHNICAL DATA SHEET

Product: -PVC plain weave double side coated Fabric (3307 1100gr/m2)

Application:

Boat fabric

Support Cloth (DIN 6000)	Polyester
Specification (DIN EN 1049-2)	30*30 per inch(panama weave)
Yarn (d) (DIN EN ISO 2060)	1000*1000 D
Type of Coating	PVC coated on both sides
Total Weight (DIN EN ISO 2286-2)	1100g/m2
Width (DIN EN ISO 2286-1)	UP TO 3.2M (Common Width:1.5,1.55,2.04,2.18m)
Tensile strength (DIN 53354)	4000/4000 N/5CM
Tear strength (DIN 53356)	450/430N/5CM
Adhesion Strength	180/5cm
Low Temperature-No Crack At	-30℃ to +70℃
Flame Retardant	NFPA701,M2,B1 as request

Packing: craft paper or PE foam, available with Hard Tube protection packing.

Features:
A: UV resistant, FR (NFPA701, B1, M2)
B: Cold resistant, Anti-Mildew
C: Glossy and Matt surface
D: Lacquered are available as requests
E: Color, weight can be customized