®ZHEJIANG DEJIA NEW MATERIAL CO.,LTD
No.1 Luhong Road, Dingqiao, Haining, Zhejiang, China. 314413
www.dejiafabric.com

TECHNICAL DATA SHEET

Product: -PVC plain weave double side coated Fabric (DCW650 650gr/m2)

Application:

Boat fabric

Support Cloth (DIN 6000)	Polyester
Specification (DIN EN 1049-2)	20*22 per inch(plain weave)
Yarn (d) (DIN EN ISO 2060)	1000*1000 D
Type of Coating	PVC coated on both sides
Total Weight (DIN EN ISO 2286-2)	650g/m2
Width (DIN EN ISO 2286-1)	UP TO 3.2M (Common Width 2.18m)
Tensile strength (DIN 53354)	2800/2500 N/5CM
Tear strength (DIN 53356)	280/280N/5CM
Adhesion Strength	160/5cm
Low Temperature-No Crack At (EN 1876/1)	-40℃ to +70℃
Thickness	0.55±0.03mm
Flame Retardant	NFPA701,M2,B1 as request

Packing: craft paper or PE foam, available with Hard Tube protection packing.

Features:
A: UV resistant, FR (NFPA701, B1, M2)
B: Cold resistant, Anti-Mildew
C: Glossy and Matt surface
D: Lacquered are available as requests
E: Color, weight can be customized

Note: These indicated technical data are based on average results. Due to production procedures deviations up to -5% can occur. All technical data are in accordance with the present standard of knowledge and give product information without legal binding. All data apply to new products. Applications suggested do not release the customer to test material for its intended application.

Please check with your distributor for the exact list of additional properties for a specific product