®ZHEJIANG DEJIA NEW MATERIAL CO.,LTD
No.1 Luhong Road, Dingqiao, Haining, Zhejiang, China. 314413
**www.dejiafabric.com**

# TECHNICAL DATA SHEET

**Product:** -PVC plain weave double side coated Fabric (DCW1450 1450gr/m2)

## Application:

Boat fabric

| | |
|---|---|
| Support Cloth ( DIN 6000 ) | Polyester |
| Specification ( DIN EN 1049-2 ) | 30*30 per inch(panama weave) |
| Yarn (d) ( DIN EN ISO 2060 ) | 1000*1000 D |
| Type of Coating | PVC coated on both sides |
| Total Weight ( DIN EN ISO 2286-2 ) | 1450g/m2 |
| Width ( DIN EN ISO 2286-1) | UP TO 3.2M<br>(Common Width: 1.55m) |
| Tensile strength ( DIN 53354 ) | 4500/4500 N/5CM |
| Tear strength ( DIN 53356 ) | 500/460N/5CM |
| Adhesion Strength | 180/5cm |
| Low Temperature-No Crack At ( EN 1876/1 ) | -40℃ to +70℃ |
| Thickness | 1.14±0.03mm |
| Flame Retardant | NFPA701,M2,B1 as request |

**Packing:** craft paper or PE foam, available with Hard Tube protection packing.

**Features**:
A: UV resistant, FR (NFPA701, B1, M2)
B: Cold resistant, Anti-Mildew
C: Glossy and Matt surface
D: Lacquered are available as requests
E: Color, weight can be customized

Note: These indicated technical data are based on average results. Due to production procedures deviations up to -5% can occur. All technical data are in accordance with the present standard of knowledge and give product information without legal binding. All data apply to new products. Applications suggested do not release the customer to test material for its intended application.

Please check with your distributor for the exact list of additional properties for a specific product